



**TELEDYNE
DEFENCE**

A Teledyne Technologies Company

Digitising Receiver

Technical Data **DR068**



Features

Broadband operation : 2-18 GHz
15-BIT output (0.5 MHz Resolution)
Pulse Amplitude, Pulse Width and TOA
50 MHz Clocking rate
60 dB Dynamic range
'VME64' Form Factor

Applications

Electronic Support Measures
Radar Warning Receivers
ECM Set-On
Airborne, Fixed Wing & Rotary
Land
Naval

Product Description

The DR068 latest Digitising Receiver builds on the strong tradition of TDL Digital Frequency Discriminators (DFD's).

The DR068 takes key performance elements from a number of existing production DFD's, integrating them for the first time into a complete digital solution suitable for military environments.

The DR068 offers the benefits of TDL's field-proven proprietary SSS discriminator tiers coupled with the latest digital technology to produce a receiver that not only measures frequency but is capable of Digital Signal Processing (DSP) of the raw frequency data.

DSP capability, is incorporated as standard; however, due to the use of state-of-the-art FPGA technology, TDL is able to adapt and add to the DSP capability to offer a DFD that is suitable for the majority of systems. In addition to measuring frequency, the DR068 also measures pulse parameters such as time of arrival (TOA), pulse width (PW) and pulse amplitude.

POP and FMOP options available on request.

Data is output as a 96 bit Pulse Descriptor Word (PDW) as three 32 bit words via the industry standard Front Panel Data Port (FPDP) connector. An optional 51 Way MDM interface is available.

The DFD is packaged in an industry standard dual slot (8HP) width plug-in format with DIN41612 interface for VME bus applications, suitable for most modern day EW suite equipment racks.

Global Defence & Security Solutions

Teledyne Defence Ltd
Airedale House
Royal London Industrial Estate
Acorn Park, Charlestown
Shipley, West Yorkshire
UK, BD17 7SW

Tel: +44 (0) 1274 531 602
Fax: +44 (0) 1274 595 724
Email: sales@fcl.com
Web: www.teledyne.com

DR068 rev 1.2
23 Aug 2007
Page 1 of 7




Electrical Specification

Parameter	Units	Min	Value Nom	Max
1 Operating Frequency Range	GHz	2.0		18.0
2 Operating + Guard Band	GHz	1.98		18.02
3 Unambiguous Frequency Range	GHz	1.98		18.02
4 Frequency Resolution	MHz		0.5 MHz	
5 Digital Frequency Resolution	Bits		15	
6 Frequency Error (RMS)	MHz			3.0
7 Frequency Peak Error	MHz			16
8 Peak Error Rate	%			0.04
9 Frequency and Amplitude Measurement Dynamic Range	dBm	-55		10
10 Typical POI at -50dBm			>99%	
11 External noise input	dBm		-70dBm	
12 Amplitude Resolution	dBm		0.5	
13 Digital Amplitude Resolution	Bits		8	
14 Amplitude accuracy	dB rms			2
15 Recovery Time	ns			500
16 RF Input Pulse Width	ns	50		CW
17 RF Input VSWR				2.1:1
18 Clock Frequency (internal)	MHz	49.5	50	50.5
19 Overload Power	dBm			20
20 Data Output format				Pulse descriptor word- frequency, amplitude, TOA, pulse width, bad data flags
21 Interfaces	Power- Data Transfer- RF input- Audio output-			VME backplane Front Panel dataport SMA Audio jack
22 Temperature Range	°C	-40		85
23 Power Supply Current +12v Rail	mA		900	
24 Power Supply Current +3.3v Rail	A		3.0	
25 Power Supply Current +5v Rail	A		1.0	
26 Power Supply Current -12v Rail	mA		400	
27 Weight (Approx.)	kg			1.5
28 Size (Approx.)				
Length	mm		175	
Width (8HP)	mm		41.14	
Height (6U)	mm		262	
29 Boot Up Time	sec		5	



Block Diagram



Environmental Performance


The unit is designed to meet the environmental conditions specified below.

Temperature

Absolute operating limits: -40°C to $+85^{\circ}\text{C}$ (standard VME rack with forced air cooling)

Storage temperature: -50°C to $+100^{\circ}\text{C}$

Thermal cycling, survival: 5 cycles to the profile shown below –





Humidity

Operational: Humidity level not exceeding 95% RH (non-condensing during operation).


Pressure

Operational range: of 0.6 to 1.4 bar.

Storage range: 0.3 to 1.4 bar.

Vibration

The unit is designed to meet the following vibration profile carried out on the worst axis: i.e. the force is perpendicular to the components.



Acceleration

Structural survival: 6.75g in all directions.

Operational: 4.5g in all directions

Shock

Survival: Terminal peak saw-tooth pulse with a peak value of 20g and duration 11 ms.

Reliability

The unit has a target MTBF of 25,000 hours for an Airborne Inhabited environment.

Electromagnetic Compatibility

The unit is designed with regard to the requirements of MIL STD 461E. Compliance can only be satisfied by careful design of the overall system particularly with regard to the interconnects between the DIFM and other parts of the system. While the design will be executed with regard to the requirements of the relevant standards, TDL cannot guarantee compliance if used inappropriately.



Connector Information

RF Input is via Front Panel sma(f) connector

Data Output via FPDP as detailed in Electrical Interface and Timing Information

DC Power via VME Backplane

Electrical Interface and Timing

The primary interface for pulse measurement information is the Front Panel Data Port. This port is designed in accordance with VITA 17-199x Rev 1.7 (24 Nov 1998).

The general operation is as described below:

- The DR068 transmits a Pulse Descriptor Word on the FPDP every time an RF pulse is detected and measured.
- The FPDP communication is one-way, however, the receiver is able to suspend transmission of PDW's by asserting the SUSPEND signal.
- The FPDP data word is 32-bit wide 'frame', a DR068 PDW is 96-bits long, therefore 3 32-bit frames are transmitted for every PDW
- The FPDP clock rate is 40MHz.
- A PDW transfer takes 5 clock cycles, therefore at 40MHz, it takes 125ns to TX a PDW.

NOTE: The DR068 has been designed and tested using a PC driven FPDP card, this card is manufactured by VMETRO (model number DPI02-FBU)

The following table defines a format for a pulse descriptor word:

Parameter	No. of bits	Resolution	Description
Parameter	No of Bits	Resolution	Maximum Value
Frequency	15		
Amplitude	8		
Pulse Width	16	5ns	327.675us
Time of Arrival	32	5ns	21.47s
Flags	6		

The format of the data frame will be as follows:

Word 0	TOA [D31:0]		
Word 1	Pulsewidth [D31:16]	Frequency [D15:1]	Spare [D0]
Word 2	Flags [D31:26]	Spare [D25:8]	Amplitude [D7:0]




Flag data is as follows:

D31	Bad Data – ambiguity	D30	Bad data – threshold
D29	Not used	D28	Not used
D27	CW Flag	D26	Not used

Front Panel Data transfer:

Each PDW will be transferred in five front panel data port clock cycles. The DR068 is the master (transmitter) the host system is the slave (receiver).

The diagram below shows a full transfer plus start of next transfer:



NOTE: Refer to Front Panel Data Port Specifications, VITA 17-199x, for details of operation of the transfer bus.

NOTES

1. The pulse width measurement will be derived from the output signal of the pulse detection circuit, i.e. it will not be the width of pulse at 3 dB points.
2. Pulse widths longer than the maximum specified will be flagged as CW. A PDW will be generated at the end of every 327.675us (with the CW flag set) until the pulse has been determined to have gone away.
3. The TOA counter will roll-over to zero every 21.47s.



**TELEDYNE
DEFENCE**

A Teledyne Technologies Company

Digitising Receiver

Technical Data **DR068**





**TELEDYNE
DEFENCE LIMITED**

A Teledyne Technologies Company

Digitising Receiver

Technical Data **DR068**

Teledyne Defence Ltd
Airedale House
Royal London Industrial Estate
Acorn Park
Charlestown
Shipley, West Yorkshire
UK, BD17 7SW

Tel: +44 (0) 1274 531 602
Fax: +44 (0) 1274 595 724
Email: sales@fcl.com
www.teledyne.com